

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>F04D 25/16</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/31937</b>
		(43) International Publication Date: 23 July 1998 (23.07.98)

(21) International Application Number: PCT/FI98/00037


(22) International Filing Date: 16 January 1998 (16.01.98)

(30) Priority Data:  
970210 17 January 1997 (17.01.97) FI(71) Applicant (for all designated States except US): ABB FLÄKT  
OY [FI/FI]; Karapellontie 12, FIN-02620 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HULKKONEN, Rauli,  
Tapani [FI/FI]; Mäntyviita 3 E 35, FIN-02110 Espoo (FI).  
VUORENMAA, Jyri-Markku [FI/FI]; Mäkelänkatu 45 D  
32, FIN-00550 Helsinki (FI). TALLGREN, Joni, Antero  
[FI/FI]; Lammasrinne 4 B 38, FIN-01710 Vantaa (FI).(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box  
148, FIN-00121 Helsinki (FI).(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,  
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE,  
GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ,  
LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW,  
MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL,  
TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO  
patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT,  
LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI,  
CM, GA, GN, ML, MR, NE, SN, TD, TG).**Published***With international search report.*

(54) Title: HIGH-PRESSURE FAN



## (57) Abstract

The invention relates to a high-pressure fan comprising a blade wheel (3, 4), a fan housing (5, 6) surrounding the blade wheel and an electric motor (1) to operate the blade wheel. To eliminate the problems related to the mounting of the blade wheel, the blade wheel (3, 4) at least mainly consists of light carbon-fibre-based composite material and is directly mounted on the shaft (2) of the electric motor (1).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

## HIGH-PRESSURE FAN

The invention relates to a high-pressure fan comprising a blade wheel, a fan housing surrounding the blade wheel and an electric motor to  
5 operate the blade wheel.

With a high-pressure fan implemented according to the prior art, having a blade wheel of steel blades with separate roller bearings, it is at best possible to achieve a pressure rise of a few dozens of kPas at one stage. When the prior art technology is applied, the high-pressure fan has to be  
10 implemented as a two-staged or multi-staged series-connected arrangement if a higher rise in the pressure is to be achieved.

The determining factor in the mechanical implementation of the high-pressure fan of the prior art is the weight and strength of the steel blade wheel. Because of the heavy blade wheel compromises have to be made as  
15 regards the dimensioning of bearings. The bearings must endure the great stress put on them by the weight of the blade wheel, and also sustain the centrifugal forces resulting from the high rotation speed, and heat production in the roller elements. For the fan to operate smoothly, the critical rotation speed of the rotor system has to be above the operating rotation speed. In  
20 practice, this results in such dimensioning in which the roller bearings used are relatively large, and the heat generated in the bearings is led away by means of an effective oil circulation lubricating system.

Due to the above-mentioned features, both the single-staged and multi-staged versions of the existing high-pressure fans have to be provided  
25 with separate bearings, either roller or slide bearings, since the bearings of the electric motor do not endure the stress caused by a steel blade wheel.

An object of the present invention is to eliminate the drawbacks described above. This is achieved with a high-pressure fan of the invention, characterized in that the blade wheel at least mainly consists of carbon-fibre-  
30 based composite material, and is mounted directly on the shaft of the electric motor.

By making the blade wheel of a high-pressure fan or its essential components of carbon-fibre-based composite material the weight of the blade wheel can be reduced to a fraction of the weight of a steel blade wheel. A  
35 blade wheel made of this material can be dimensioned to be as strong as the steel blade wheel or even stronger. The light composite blade wheel can be

mounted directly on the shaft of a standard electric motor without the stress on the bearings increasing too high. By means of an AC inverter a fan implemented in this way can be rotated up to the maximum rotation speed given by the manufacturer of the bearings.

5           When an electric motor is preferably implemented with a shaft going through it, and a blade wheel of composite material is mounted on the shaft of the motor at its both ends, the axial forces generated in the blade wheels will cancel each other out, and hence it will be possible to use the standard bearings of the electric motor. The sides of the fan implemented in this way  
10 can be interconnected with an intermediate channel, i.e. it is possible to provide a two-staged fan which replaces the conventional version implemented with two separate fans. The fan arrangement can naturally be used as two separate series-connected fans without the above-mentioned intermediate channel.

15           Compared with the conventional two-staged fan implemented with two separate fans, the two-ended fan of the present invention allows to dispose of 4 bearings with their casings and circulation lubricating units as well as of couplings between the electric motor and the blade wheel arrangement since no separate bearings are needed. Furthermore, the arrangement is  
20 compact, a simple and cheap steel bed can be used as its bed, and no multi-level bed arrangements are needed in the installation.

In the following, the invention will be described by means of one preferred embodiment with reference to the accompanying drawing, which illustrates a perspective of a high-pressure fan of the invention.

25           The high-pressure fan illustrated in the drawing has as its source of motive power an electric motor 1, comprising a rotor shaft 2 going through it, i.e. a shaft the ends of which project at both sides of the motor 1. A light blade wheel 3 and 4, which at least mainly consists of carbon-fibre-based composite material, i.e. at least its blades 3a, 4a and end plates 3b, 4b are of said  
30 material, is mounted directly onto the both ends of this shaft without separate bearings. The hub 4c of the blade wheel may also be of some other material, e.g. steel. This direct mounting means that only the bearings of the electric motor 1 are used for mounting the whole above-mentioned arrangement. The blade wheels 3 and 4 are surrounded by fan housings 5 and 6, and the  
35 pressure opening 9 of the first housing 5 is connected to the suction opening 9 of the second housing 10 with an intermediate channel 10.

Reference number 11 denotes the pressure opening of the second housing 6, and reference number 12 the suction opening of the first housing. The view of the housings 5 and 6 illustrated in the drawing is partially sectional. The whole fan arrangement described above is placed on a simple  
5 steel bed 8.

Due to the connecting intermediate channel 7 the fan illustrated in the drawing functions as a two-staged fan. If this intermediate channel 7 is removed, the fan arrangement will function as two separate series-connected fans.

10 The invention has been described above only by means of one preferred embodiment. One skilled in the art can, however, implement the fan of the invention and its details in several alternative ways within the scope of the appended claims. For example, there could be a blade wheel only at one end of the motor, and the axle could be implemented in such a way that it  
15 does not go through the motor. Correspondingly, there could be several blade wheels at both ends of the motor or only at one end of it.


## CLAIMS

1. A high-pressure fan comprising a blade wheel (3, 4), a fan housing (5, 6) surrounding the blade wheel and an electric motor (1) to operate the blade wheel, **characterized** in that the blade wheel (3, 4)  
5 at least mainly consists carbon-fibre-based composite material and is mounted directly on the shaft (2) of the electric motor (1).

2. A high-pressure fan as claimed in claim 1, **characterized** in that the electric motor (1) has a shaft (2) going through it, and at the both ends of the electric motor (1) there is a blade wheel (3, 4) arranged directly on  
10 the shaft (2) of the motor.

3. A high-pressure fan as claimed in claim 2, **characterized** in that the fan housings (5, 6) surrounding the blade wheels (3, 4) are interconnected with an intermediate channel (7).

4. A high-pressure fan as claimed in claim 3, **characterized**  
15 in that the intermediate channel (7) leads from the pressure opening (9) of one of the housings (5) to the suction opening (10) of the other housing (6).



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/FI 98/00037

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F04D 25/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F04D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	GB 920188 C (SOCIETE ANONYME DES ETABLISSEMENTS NEU), 6 March 1963 (06.03.63), figure 1 --	2,3
Y	US 1014321 A (D.B. MINOR), 14 January 1912 (14.01.12), figure 1 --	1,2,3,4
Y	US 2903182 A (S.H. DOWNS), 8 Sept 1959 (08.09.59), figure 1 --	3,4
Y	US 4746266 A (KIRCHNER ET AL), 24 May 1988 (24.05.88), figure 1 --	1,2,3,4



Further documents are listed in the continuation of Box C.



See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance  
 "B" earlier document but published on or after the international filing date  
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  
 "O" document referring to an oral disclosure, use, exhibition or other means  
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 April 1998

Date of mailing of the international search report

18 -04- 1998

Name and mailing address of the ISA/  
 Swedish Patent Office  
 Box 5055, S-102 42 STOCKHOLM  
 Facsimile No. +46 8 666 02 86

Authorized officer

Lena Nilsson  
 Telephone No. +46 8 782 25 00



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 98/00037

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5464325 A (ALBRING ET AL), 7 November 1995 (07.11.95), figure 3  -----	1,2,3,4

# INTERNATIONAL SEARCH REPORT

Information on patent family members

02/03/98

International application No.

PCT/FI 98/00037

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
GB	920188	C	06/03/63	NONE	
US	1014321	A	14/01/12	NONE	
US	2903182	A	08/09/59	NONE	
US	4746266	A	24/05/88	DE 3631942 A,C EP 0261490 A,B	07/04/88 30/03/88
US	5464325	A	07/11/95	DE 4321173 A,C EP 0635643 A	12/01/95 25/01/95